

ENHANCED CATEGORY5 350MHZ SOLID PLENUM

CBL-C59PXX-AM

CABLE CONSTRUCTION			8903100009
Specification No.:	1/0.54BA *4PR Enhanced 350Mhz		P/N. LFS1800MP053ZZ
UL File NO.:	E129760	CSA File NO.: LL80671	Date: 3/15/2000
	CMP--CAT5	CSA Style: II A/B	Draw NO.: CAT5P.XLS
Construction Item			Construction ItemA
Conductors	Construction AWG	AWG	24
	Material	--	Bare copper
	Conductors No:	--	1
	Conductors AWG:	AWG	24
	O.D.	mm	0.517 Ref
Insulators	Material	--	FEP (TEFLON)
	Diameter	mm	0.90+/-0.05
	Average Thickness	mm	0.192Ref
	Color	--	AS COLOR CODE
Inner-Layer	Direction	--	Right (S)
	Diameter	mm	1.80
Layer	Pitch	mm	123Ref
	Direction		Right (S)
	Diameter	mm	4.00Ref
Outside Jacket	Material	--	Flame-Retardant PVC
	Diameter	mm	5.3+/-0.21
	Average Thickness	mm	0.65Ref
	Extrusion	--	Semi-tubing
	Surface	--	Plane
	Color	--	
Marking	SPACE SHUTTLE (UL) E129760 CMP 24AWGX4P AND ETL EIA/TIA 568A 4UTP CSA LL80671		
	FT6 CAT5 ----- 350MHZ		